Printing date 20.11.2012

Version number 13

Revision: 20.11.2012

SECTION 1: Identification of the substance/mixture and of the company/undertaking • 1.1 Product identifier

· Trade name: Water Repellant Spray

· Article number: 2420001-2420099

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

• Application of the substance / the preparation Impregnation spray for leather Impregnation spray for textiles

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Dumco B.V. Nies van der Schansstraat 1 5161 CE Sprang-Capelle Nederland tel. 0416-669977 fax.0416-278735

www.dumco.nl info@dumco.nl

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Classification according to Directive 67/548/EEC or Directive 1999/45/EC		
STOT SE 3	H336 May cause drowsiness or dizziness.	
Skin Irrit. 2	H315 Causes skin irritation.	

Xi; Irritant
R38: Irritating to skin.
F+; Extremely flammable
R12: Extremely flammable.
N; Dangerous for the environment
P51/53: Toxic to acuatic organisms, may equed long term adverse effects in the acuatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Printing date 20.11.2012

Version number 13

Revision: 20.11.2012

(Contd. of page 1)

Trade name: Water Repellant Spray

Harmful: may cause lung damage if swallowed.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant

F+ *Extremely flammable N Dangerous for the environment*

· Risk phrases:

- *12 Extremely flammable.*
- *38 Irritating to skin.*
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe spray.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

- Keep out of the reach of children
- Vorsicht! Unbedingt beachten!

Gesundheitsschäden durch Einatmen möglich! Nur im Freien oder bei guter Belüftung verwenden! Nur wenige Sekunden sprühen! Großflächige Leder- und Textilerzeugnisse nur im Freien besprühen und gut ablüften lassen! Von Kindern fernhalten!

- · Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

D'angerous components.		
CAS: 64742-49-0		50-100%
EINECS: 265-151-9	🗙 Xn R65; 🗙 Xi R38; 🔥 F R11; 🏪 N R51/53	
Reg.nr.: 01-2119475514-35-xxxx		
	🛞 Flam. Liq. 2, H225; 🚷 Asp. Tox. 1, H304; 🚯 Aquatic	
	🚸 Flam. Liq. 2, H225; 🚸 Asp. Tox. 1, H304; 🚸 Aquatic Chronic 2, H411; ᡝ Skin Irrit. 2, H315; STOT SE 3, H336	
	(Con	td. on page 3)

Printing date 20.11.2012

Version number 13

Revision: 20.11.2012

Trade name: Water Repellant Spray

		(Contd. of page 2
CAS: 75-28-5	isobutane	10-25%
EINECS: 200-857-2	▶ F+ R12	
	🐼 Flam. Gas 1, H220; 🔗 Press. Gas, H280	
CAS: 74-98-6	propane	10-25%
EINECS: 200-827-9	F + R12	
	🛞 Flam. Gas 1, H220; 🔗 Press. Gas, H280	
CAS: 106-97-8	butane	2.5-10%
EINECS: 203-448-7	▶ F+ R12	
	🚸 Flam. Gas 1, H220; 🔗 Press. Gas, H280	
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	<i>≤</i> 2.5%
EINECS: 265-185-4	X <i>N R</i> 65	
	R52/53-66	
	🚸 Asp. Tox. 1, H304; Aquatic Chronic 3, H412	
• Additional information: F	or the wording of the listed risk phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation:
- Supply fresh air; consult doctor in case of complaints. Take affected persons into fresh air and keep quiet.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly. Immediately remove any clothing soiled by the product.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information
- Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.

(Contd. on page 4)

GB

Printing date 20.11.2012

Version number 13

Revision: 20.11.2012

(Contd. of page 3)

Trade name: Water Repellant Spray

 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

- *Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin and eyes.*
- · Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°*C*, *i.e. electric lights. Do not pierce or burn, even after use.*

Do not spray onto a naked flame or any incandescent material.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles:
- Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Recommended filter device for short term use: Filter AX

(Contd. on page 5)

GB -

Printing date 20.11.2012

Version number 13

Revision: 20.11.2012

(Contd. of page 4)

Trade name: Water Repellant Spray

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Material of gloves
- Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.45~\text{mm}$

- \cdot Penetration time of glove material
- ≥240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physic General Information	cal and chemical properties
· Appearance:	
Form:	Aerosol
Colour:	Colourless
· Odour:	Petrol-like
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	>200°C
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Density at 20°C:	0.61621 g/cm ³
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Organic solvents:	99.2 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Aldehyde

(Contd. on page 6)

GB

Printing date 20.11.2012

Version number 13

Revision: 20.11.2012

Trade name: Water Repellant Spray

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity:

· LD/LC50 values relevan	t for classification:
--------------------------	-----------------------

64742-49-0 Naphtha (Erdöl), mit Wasserstoff behandelte leichte, (Nota P)

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rab)
Inhalative	LC50/4 h	>5 mg/l (rat)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

Vapours have narcotic effect.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64742-49-0 Naphtha (Erdöl), mit Wasserstoff behandelte leichte, (Nota P)

EC50 1-10 mg/l (daphnia)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

 \cdot European waste catalogue

16 05 04 gases in pressure containers (including halons) containing dangerous substances

15 01 04 metallic packaging

(Contd. on page 7)

(Contd. of page 5)

Version number 13

Revision: 20.11.2012

Trade name: Water Repellant Spray

*

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	UN
14.1 UN-Number	
ADR, IMDG, IATA	1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG	
Class	2.1
Label	2.1
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substance
	Naphtha (petroleum), hydrotreated light
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	- -
EMS Number:	F- D , S - U
14.7 Transport in bulk according to Annex MARPOL73/78 and the IBC Code	: II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	LQ2
	$2^{\tilde{\sim}}$

(Contd. of page 6)

Printing date 20.11.2012

Version number 13

Revision: 20.11.2012

Trade name: Water Repellant Spray

	(Contd. of page 7)
· Tunnel restriction code	D
· UN ''Model Regulation'':	UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R38
- Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

 \cdot * Data compared to the previous version altered.